



Trusted for Decades. Ready for Tomorrow.

Typical Specifications for 6 MHz TV Standard

Model Number	VF6E15F
Frequency	54 - 88 MHz
Average Power Handling ₁	≤7 kW - 15 kW
Type	Reflective
Response Curve	Non Critical (Full Mask)
Temperature Compensated	Yes
VSWR	<1.1
Max. Altitude ₂	10,000 feet (3,050m)
Attenuation 6 MHz ATSC	
F0	<0.2 dB
F0 ± 2.69 MHz	<0.35 dB
F0 ±3.00 MHz	N/A
F0±3.25 MHz	N/A
F0 ±3.50 MHz	>0.05 dB
F0 ± 4.50 MHz	>11.6 dB
F0 ± 6.00 MHz	>30 dB
F0 ± 9.00 MHz	>64 dB
Number of Poles	6
Group Delay Variation	<150 nS over passband
Hybrids	N/A
Connectors	1-5/8" EIA/ 3-1/8" EIA
Temperature Stability	≈10 kHz/°F
Blowers & Shrouds	No
Ambient Temperature	68°F (20°C) to 95°F (35°C)
Storage Temperature	32°F (0°C) to 122°F (50°C)
Ambient/ Storage Humidity	0-98% non condensing
Material	Al with Invar rods
Dimensions (L x W x H)	47" x 31.4" x 55" (1.2m x 0.8m x 1.4m)
Weight	503 lbs (228 kg)
Applications	ATV/DTV