



### Specifications:

|                          |                              |
|--------------------------|------------------------------|
| Dimensions               | 3.5" H x 19.0" W x 10.75" D  |
| Input Power Requirements | 110-230VAC @ 50/60Hz         |
| Input Power Consumption  | 40W (controller only)        |
| Interlock Rating         | 3A @5-253VAC                 |
| Storage Temperature      | -25 to 85 °C (-13 to 185 °F) |
| Operating Temperature    | -15 to 50 °C (5 to 122 °F)   |
| Weight                   | 6.0 pounds                   |

**AVAILABLE  
TODAY**

**Manufactured in the USA**

The Dielectric RF Scout Plus monitors RF transmission system VSWR and forward power and is designed to aid in detecting VSWR problems as they develop. In many cases this will allow the transmitter operator to detect and remedy transmission system issues which may be contributing to elevated VSWR before they affect operations. The unit continuously monitors line forward and reflected power and utilizes a logic controller in order to calculate VSWR. The system displays the values and can store data and alarms in internal memory. User settable alarm levels are accessible for all alarms. Additionally, the system can be configured to monitor transmission line pressure and temperature.

*Please see the Dielectric website for a complete copy of the IB (Instruction Bulletin)*

**Trusted for Decades. Ready for Tomorrow.**