



3" low loss air dielectric cable, UV resistant black PVC Jacket applicable to both outdoor and indoor applications.

FEATURES / BENEFITS

• **Low Attenuation**

The low attenuation of this coaxial cable results in highly efficient signal transfer in your RF system.

• **Complete Shielding**

The solid outer conductor of this coaxial cable creates a continuous RFI/EMI shield that minimizes system interference.

• **Low VSWR**

Standard and low VSWR versions of this coaxial cables contribute to low system noise.

• **Outstanding Intermodulation Performance**

Coaxial cable's solid inner and outer conductors virtually eliminate intermods. Intermodulation performance is also guaranteed by the state-of-the-art manufacturing process at the factory.

• **High Power Rating**

Low attenuation, outstanding heat transfer properties and temperature stabilized dielectric materials enable this cable to provide long operating life at high transmit power levels.

• **Wide Range of Application**


Air cables are good choices for telecom, broadcasting, radar and HF defense applications.

• **Plenum Rated**

PVC jacket prevents fire from spreading, enables JPLB cables to meet and exceed all applicable plenum standards of flame travel and smoke.

• **Reinforced Jacket to Sustain Outdoor Applications**

Special additives in the jacketing compound improve the outdoor durability of the PVC jacket by minimizing the surface degradation caused by sunlight and other UV sources.



3" Air Dielectric Coaxial Cable

[External Document Links](#)

[Notes](#)

Technical features

APPLICATIONS

Applications	TV & Radio	HF Defense	Cable Solutions
--------------	------------	------------	-----------------

STRUCTURE

Size		3
Jacket Option		Black
Inner Conductor Diameter	mm (in)	29.3 (1.15)
Inner Conductor Material		Corrugated Copper Tube
Dielectric Diameter	mm (in)	63.5 (2.5)
Dielectric Material		Helical Polyethylene Spacer
Outer Conductor Diameter	mm (in)	72.4 (2.85)
Outer Conductor Material		Corrugated Copper
Jacket Diameter	mm (in)	76 (2.992)
Jacket Material		UVR PVC (UltraViolet Resistant PolyVinylChloride)
Cable Type		Air-Dielectric, Corrugated



TESTING AND ENVIRONMENTAL

Fire Performance		Flame Retardant, Plenum Rated
Flame Retardant Jacket Specifications		Meet/Exceeds Steiner Tunnel Test Method UL 910, NEC 820-53 (a) CATVP, NFPA-262
Installation Temperature	°C(°F)	-25 to 60 (-13 to 140)
Storage Temperature	°C (°F)	-60 to 85 (-76 to 185)
Operation Temperature	°C(°F)	-40 to 85 (-40 to 185)

ELECTRICAL SPECIFICATIONS

Impedance	Ω	50 +/- 0.5
Maximum Frequency	GHz	1.63
Velocity	%	96
Capacitance	pF/m (pF/ft)	66.6 (20.3)
Inductance	uH/m (uH/ft)	0.167 (0.051)
Peak Power Rating	kW	640
RF Peak Voltage	Volts	8000
Jacket Spark	Volt RMS	8000
Inner Conductor dc Resistance	Ω/1000 m (Ω/1000 ft)	0.39 (0.12)
Outer Conductor dc Resistance	Ω/1000 m (Ω/1000 ft)	0.16 (0.05)
Return Loss (VSWR) Performance		Standard
Min. Return Loss (Max. VSWR)	dB (VSWR)	Typical 20.8dB (1.2 VSWR) or better within the operation bands of most global frequency ranges. Contact factory for options in your specific frequency band.
Phase Stabilized		Phase stabilizing, phase matching, and connector assembly services are available upon request.
Temperature & Power		Standard

MECHANICAL SPECIFICATIONS

Cable Weight, Nominal	kg/m (lb/ft)	2.44 (1.64)
Minimum Bending Radius, Single Bend	mm (in)	270 (11)
Minimum Bending Radius, Repeated Bends	mm (in)	760 (30)
Bending Moment	Nm (lb-ft)	145 (107)
Tensile Strength	N (lb)	1800 (405)
Recommended / Maximum Clamp Spacing	m (ft)	0.8 / 1.2 (2.75 / 4)



ATTENUATION @ 20°C (68°F) AND POWER RATING @ 40°C (104°F)

Frequency, MHz	dB per 100m	dB per 100ft	Power, kW
0.5	0.03	0.01	596
1	0.04	0.01	421
1.5	0.05	0.02	343
2	0.06	0.02	297
10	0.13	0.04	132
20	0.18	0.06	92.30
30	0.22	0.07	74.90
50	0.29	0.09	57.40
88	0.39	0.12	42.80
100	0.42	0.13	40
108	0.44	0.13	38.40
150	0.52	0.16	32.20
174	0.56	0.17	29.80
200	0.61	0.18	27.70
300	0.75	0.23	22.20
400	0.88	0.27	19
450	0.94	0.29	17.80
500	1	0.31	16.80
512	1.01	0.31	16.60
600	1.11	0.34	15.20
700	1.21	0.37	13.90
800	1.30	0.40	13
824	1.33	0.40	12.70
894	1.39	0.42	12.10
900	1.40	0.43	12.10
925	1.42	0.43	11.90
960	1.45	0.44	11.60
1000	1.48	0.45	11.40
1250	1.69	0.52	10
1500	1.88	0.57	9.04
1700	2.03	0.62	8.39